



- >> 15"/17" LCD with Touch Screen
- >> Supports Intel P4 LGA775 CPU
- >> Built in Full I/O & PCI Slots
- >> Option PCI-E x16 graphic card



Easy Maintenance
[PC Components]



Built-in
multi-media I/O

Application: Photokiosk



Application: Retail



Specification

IT-2100



System

Motherboard Type	Pentium IV
Form Factor	u-ATX Form
System Chipset	Intel G31+ ICH7
CPU Supporting	Intel Pentium IV Processors (S775) Celeron Dual Core / Core 2 Duo / Core 2 Quad default E1400/Celeron Dual Core
CPU FSB	800/1066/1333/1600 MHz
DIMM Socket	Two 240-PIN DIMM DDRII SDRAM DDRII/667 up to 4GB; default 1GB
Audio	Realtek Audio Code
LAN Controller	10/100/1000x 1
I/O Connector	Serial Portx 3 (2x by addition PCI I/O card) Parallel Portx 1 USB Portx 4 PS/2 Mini DIN K/B Port & Mouse Port VGA Port RJ-45 Ethernet Port Audio Line-in/out and Mic-in Jacks
Optional Device	* MSR & VFD * PCI-E x16 Graphic card * E7400 / Core 2 Duo CPU

Mechanical

Touch	default Taiwan 5W Resistive Touch or ELO
Device	1.44 MB FDDx 1 (optional Card Reader) 3.5" IDE HDDx 1 (or Optional SATA HDD) optional CD-ROM /CD-RW /DVD-ROM
Power Supply	Internal 250W ATX Power Supply
Dimension	431 (W)x 293 (D)x 425 (H) mm

Display

Size	15" / 17" TFT LCD Screen
Contrast Ratio	450 : 1 / 450 : 1
Brightness	250cd/m ²
Resolution	1024x 768 / 1280x 1024

Puritron Technology Inc.

TEL: +886-2-2914-7298

FAX: +886-2-2915-6795

E-mail : info@puritron.com.tw

Website : www.puritron.com.tw