



Trusted Point-of-Service

15" ULV Fanless POS

NEW Releasing !

- >> True Fanless design
- >> Glossy piano painting bezel
- >> Compact & slim AIO POS terminal
- >> Innovative and Luxury whole new design

■ **KS-150**



Piano-glossy painting front bezel



Front USB with slide cover



Docking rear cover



Specification

System

Motherboard Type	KS-700B	KS-700P	KS-700A
Product Name	KS-150B	KS-150P	KS-150E
CPU	P4 / Celeron M-1.0GHz	P4 / Celeron M-1.0GHz	Atom N270
Core Logic	Intel 852GM + ICH4	Intel 910gmle+ICH6M	Intel 945GSE + ICH7M
DIMM Socket	DDR RAM(Up to 1GB)	DOR2 RAM(Up to 2GB)	DOR2 RAM(Up to 2GB)
OS	Win2000, NT, Win XP, Embedded XP(XPe), WinCE, WEPOS		

Display

LCD Size	15"		
Brightness	250 nits		
Resolution	1024 x 768		
Touch Screen	Default Taiwan 5-wire Resistive Touch or Option ELO 5W Resistive touch		

Storage

Device	1 x IDE 2.5" 80/160GB	1 x SATA 2.5" 80/160GB
--------	-----------------------	------------------------

IO Connector in rear

Power Jack	DC IN JACK Port		
PS/2	1x 6-pin mini DIN		
USB	4x USB 2.0 External		
RS232	3x	4x	4x
VGA	1x DB-15, female		
Power Port	1x 12VDC Output (700mA)		
Cash drawer Port	1x RJ11, 12VDC		
Audio Line	1x Mic In , 1 x Audio Out		
LAN	2x RJ45, 10/100/1000 BASE-T , supports wake on LAN		

IO Connector in front

USB	2 x USB 2.0 External		
-----	----------------------	--	--

Internal IO(for Touch/MSR/VFD/CRND)

USB	2x	2x	2x
RS232	1x	2x	2x
Compact Flash	N/A	1x	1x
Printer Port	1x	1x	N/A

Others

Power Supply	60W Adapter
Color	Black/White/Red
Certification	FCC, CE, RoHS

Option

MSR (Track 1-3) ; VFD (ICD2002F-AR1AU)

Puritron Technology Inc.

TEL: +886-2-2914-7298

FAX: +886-2-2915-6795

E-mail: info@puritron.com.tw

Website: www.puritron.com.tw