PURITRON
ISO 9001 Ceritified

CE FC

DC-DC
9-36V

Trusted Point-of-Service

PT-Series

DC-DC Fanless Panel PC

NEW Releasing !

15" DC-DC(9-36V) Fanless Panel PC
Stainless front bezel
Intel ULV low power

PT-150PF-DC

Built-in Speaker

IP-54
Water Splash Compliant



Wide 9-36V DC Input

Specification

PT-150PF-DC

System

Motherboard Type	Intel
Form Factor	Mini-ITX
System Chipset	Intel 852GM/Intel ICH4
CPU Supporting	Intel ULV 1GHz(non L2 Cache)
CPU FSB	400MHz
DIMM Socket	One 184-PIN DIMM DDR266 SDRAM,
	Up to 1GB, default 512MB
Graphic	Integrated Intel 852GM GMCH
Audio	Realtek AC'97 Codec
LAN Controller	Dual LAN
I/O Connector	Realtek 8100C 10/100 Base-T Ethernet, RJ-45x2
	Serial Port× 3
	(or optional Serial Port × 1 & Paralle× 1)
	USB Port× 4; VGA Port× 1;
	Cashdrawer Portx1
	PS/2 Mini DIN Keyboard Port & Mouse Port
	Audio Line-in/out and Mic-in Jacks

Mechanical

Touch	default Taiwan 5-wire Resistive Touch or ELO by option
Device	2.5" IDE HDD× 1 (Support Ultra DMA-66/100), default 40GB
Output (Max)	60W (12V@5A Max.)
Input	9-36V DC
Bezel	Stainless(Optional Black Plastic Bezel)
Dimension	280x380x82mm

Display

Size	15" TFT LCD
Contrast Ratio	450 : 1
Brightness	250cd/m²
Resolution	1024× 768

Puritron Technology Inc.
TEL: +886-2-2914-7298 FAX:+886-2-2915-6795
E-mail : info@puritron.com.tw Website : www.puritron.com.tw